

# COMET PUMP (6513290100)



SKU: 210 TW40100S

**Flow 16.1L/min**  
**Pressure 10000psi**  
**Speed 1450rpm**



Comet Pump #

| Code         | Type | RPM  | Flow rate |     | Pressure |      | Power |      | Weight |
|--------------|------|------|-----------|-----|----------|------|-------|------|--------|
|              |      |      | l/min     | bar | psi      | hp   | kW    | kg   |        |
| 210 TW35100S |      | 1450 | 14,6      | 700 | 10153    | 24,4 | 17,9  | 34,5 |        |
| 210 TW40100S |      | 1450 | 16,1      | 700 | 10153    | 26,9 | 19,8  | 34,5 |        |



Head  
material  
legend  
Stainless  
Steel

**Pump Specs:**

- GPM: 3.6
- PSI: 10000
- RPM: 1450
- Shaft Diameter: 30mm
- Piston Diameter: 15mm

**Pump Features:**

- 1/2" FPT Inlet, 1/2" FPT Outlet (Female 60° cone seat)
- Solid Shaft 30mm for Belt Drive, Gearbox or Flex Couplers
- Right or Left Hand Mounting Available Crankcase: Die-Case Aluminum Alloy for Protection Against Corrosion
- Top-Quality and oversized conical Roller Bearings with covers for adjusting the pre-load
- Piston Guides are Heat Treated Stainless Steel
- Highly Efficient Stainless Steel Check Valves
- Large Oil Capacity Dissipates Heat and Improves Lubrication for Longer Life
- Plungers with Tungsten carbide coating, highly corrosion and abrasion-proof
- Heavy Duty up to 11600 PSI
- Stainless Steel Manifolds



# COMET PUMP (6513290100)



- High Volume up to 3.6 GPM
  - Special Aluminum Alloy Conrods made in a double piece
  - Long Life Seals
- 

