

# SWITCHBLADE DEUCE BODY, 2 NOZZLES



SKU: 165 2035

## Dual Nozzle Body, 1/2" FNPT Inlet, 30 Mesh

|                     |                     |
|---------------------|---------------------|
| Max. Inlet Pressure | 220 bar (3,200 psi) |
| Max. Water Temp.    | +82°C (180°F)       |
| Housing Material    | Stainless Steel     |
| Coating Material    | Urethane            |

The Switchblade™ nozzle is designed and engineered for the rugged Hydro-Excavation industry. These heavy-duty, high-impact nozzles allow you to cut through dirt faster while using dramatically less water.



- **Performance** – Complete jobs faster with more runtime and less downtime. 2 x 0° solid stream nozzles provide greater impingement, allowing you to cut through soil faster while using dramatically less water. The Switchblade's long, linear flow path is ideally suited for trenching applications.
- **Durability** – These heavy duty, high impact nozzles are constructed with stainless steel housings and tungsten carbide wear surfaces to withstand harsh environments and provide longer life than stainless steel nozzle tips.
- **Safety** – Non-conductive urethane coating on the nozzle body protects the operator and sensitive underground utilities.
- **Flexibility** – Individual, replaceable, color-coded nozzle pills allow you to change water flow rate and pattern based on current soil conditions.

