

The BE misting fan combines a high pressure, centrifugal misting system with a blower fan. That means there are no misting nozzles and thus no possibility of clogging from hard water build-up.

There are 3 fan speeds to choose from — low, medium, and high with respective RPMs of 1400, 1500, and 1700. This outdoor fan has a very wide head, at 650mm across, and when combined with the oscillation option, is highly effective at cooling industrial, horticulture, agriculture, and commercial operations.

The fan is fed by a huge 41 Litre water storage tank and includes a no mess drip collector. You can also control the mist volume output to help get you through the heat this summer.

## FEATURES

- Adjustable height to 1.8 m and 3 speed operation
- Large water storage tank
- No mess drip water collector
- Heavy duty base for safety and stability
- Fixed wheels and lockable castors
- Nozzle-less misting hub technology (high-speed centrifugal atomizer) is guaranteed not to clog
- Adjustable dial to control misting volume
- Automatic shut-off when water tank is empty
- Suitable for cooling people, stockbreeding and greenhouse applications
- Mist Jet distance: 8 - 10 m

## SPECIFICATIONS

<b>Type</b>	Industrial Misting Fan
<b>Size</b>	650 mm (26")
<b>Voltage:</b>	240 V/50HZ
<b>Motor Power:</b>	260 W
<b>Amp Draw:</b>	1.1 A
<b>Fan Speeds:</b>	3
<b>Fan Blades:</b>	3 Blade, 650mm Cast Steel
<b>Oscillation Angle:</b>	90°
<b>Fan Tilt Adjustment:</b>	30°
<b>Cable Length:</b>	2 m
<b>Plug Type/Spec:</b>	10A - AU SAA Type
<b>Air Output:</b>	138 m <sup>3</sup> /min
<b>Air Volume:</b>	4,873 CFM
<b>Air Velocity:</b>	8 m/sec
<b>Effective Area:</b>	200 m <sup>2</sup>
<b>Water Tank:</b>	41 L
<b>Water Consumption:</b>	5 L/hr
<b>Noise Level:</b>	68 dBA
<b>Net Weight:</b>	23 kg
<b>Certifications:</b>	SAA/AS, tropic-proofed
<b>Warranty:</b>	1 Year
<b>Product Dimensions:</b>	L 70 cm x W 55 cm x H 178 cm



PIN IMF66

**SCAN QR CODE  
FOR PRODUCT  
WEBSITE PAGE**

