

Electric Twin Boiler Hot Water



State of the art hot water high efficiency pressure washer for intensive use. Top efficiency for heavy duty industrial cleaning. Equipped with 2 high efficiency boilers with a refractory cement base and stainless-steel boiler head and cylinder. This type of unit is well used in situations where a high hot water flow is needed for a high degreasing power. Particularly suitable for washing large tanks and containers and other applications where a large hot water volume is required.

Series Options

| ROBOT 2 | Pres | Pressure | | Flow Rate | | R.P.M. | Water temperature | | Weight | Box Dimensions | | Quantity/Container | | Machine Dimensions |
|-------------------|------|----------|-------|-----------|----|--------|----------------------|--------|--------|-------------------|-----|--------------------|-------|-----------------------|
| | bar | PSI | Lt/h | gph | HP | | °C | °F | kg | LxWxH (cm) | / 2 | 20 ft | 40 ft | LxWxH (cm) |
| 108 ROBOT2 150.30 | 150 | 2.200 | 1.800 | 476 | 10 | | | | 367 | | | | | |
| 108 ROBOT2 150.42 | 150 | 2.200 | 2.520 | 663 | 15 | 1.450 | 40/150 | 70/350 | 372 | 146x89x137 | | 8 | 16 | 98x83x119 |
| 108 ROBOT2 200.30 | 200 | 3.000 | 1.800 | 476 | 15 | | | | 372 | | | | | |

TSI = Intelligent Total Stop - Arresto Totale Intelligente





Electric Twin Boiler Hot Water

Triplex pump with ceramic plungers connecting rod system, brass head pump. Pressure regulator. Fuel, water and detergent filters. Pressure gauge and thermostat. Safety valve.

TSI security system including: (1) time delayed auto stop start 3 seconds delay on boiler start-up; (2) stop for lack of water; (3) stop for leak detection; (4) stop after 1 hour in total stop, (5) burner shutdown in case of lack of fuel.

10/15HP IE2 High efficiency










Two 230V independent high efficiency vertical stainless steel AISI 430 boilers with refractory cement base. A photocell is available as an optional feature.

24 V control panel.

Fuel filter

Galvanized steel chassis with fuel and water tank.

HP detergent suction probe.







Stadard Accessories











OPTIONAL

Optional Accessories



Pipe cleaning rotating nozzle



Double nozzle carrier (supplied without nozzles)



Kit rotating nozzle



Sand blasting kit



Exhaust smoke tube adapter



H.P. connection sealing



15 mts. hosereel kit

S.S. Sand blasting tank

Water softner